


# Gama Suelo-Techo



5,2 kW	AVT52UR4RSA4
7,1 kW	AUV71UR4RFA4

9,0 kW	AUV90UR4RFB4
10,5 kW	AUV105UR4RAB4

12,5 kW	AUV125UR4RTC5
14,0 kW	AUV140UR6RPC4
17,5 kW	AUV175UR6RPC4



NUEVO DISEÑO



CAUDAL AIRE 3D



FRESH-AIR INTAKEA



ON/OFF FUNTION



BUILT-IN DRAIN PUMP OPTIONAL



MULTIPLE INSTALLATION TYPES



AUTO RESTART

## Gama Comercial Suelo-Techo

			AVT52UR4RSA4	AUV71UR4RFA4	AUV90UR4RFB4
Unidad interior			AVT52UR4RA4	AUV71UR4RA4	AUV90UR4RB4
Unidad exterior			AUW52U4RS4	AUW71U4RF4	AUW90U4RF4
Capacidad	Frío Nominal (Mín-Máx)	Frig/h	4541(1273—4730)	5934(2150—6794)	7568(3010—7740)
	Frío Nominal (Mín-Máx)	kW	5280 (1480-5500)	6900 (2500-7900)	8800 (3500-9000)
	Calor Nominal (Mín-Máx)	Kcal/h	4816(1437—5470)	6708(1892—7912)	7740(2580—7912)
	Calor Nominal (Mín-Máx)	kW	5600(1670-6360)	7800 (2200-9200)	9000 (3000-9200)
Consumo Nominal			6,3	6,1	6,1
	SEER (Rango)		4,4	4,2	4,1
	SCOP (Rango)*		A++	A++	A++
Clasificación Energética	Frío	Frig/h	A+	A+	A+
	Calor	Kcal/h	800/690/600	1100/950/800	1450/1120/900
Unidad Interior	Caudal de aire (A/M/B)	m³/min	40/36/33	51/48/45	49/43/40
	Nivel sonoro (A/M/B)	dB(A)	57	63	65
	Potencia sonora	dB(A)	990×680×230	990×680×230	1285×680×230
	Dimensiones An x Al x Fon	mm	30.0/35.0	30.0/35.0	37.0/44.0
	Peso Neto/con embalaje	kg			
Unidad Exterior			51	56	51
	Nivel sonoro (A)	dB(A)	64	68	67
	Potencia sonora	dB(A)	810×580×280	860×670×310	860×670×310
	Dimensiones An x Alx Fon	mm	36.0/40.0	49.0/53.0	49.0/53.0
	Peso Neto/con embalaje	kg	R32	R32	R32
Refrigerante	Gas		0,97	1,40	1,45
	Carga Kg		*6.35/*12.7(1/4'/1/2')	*9.52/*15.88(3/8'/5/8')	*9.52/*15.88(3/8'/5/8')
Diám. tuberías líquido/gas	mm/pulg		*6.35/*12.7(1/4'/1/2')	*9.52/*15.88(3/8'/5/8')	*9.52/*15.88(3/8'/5/8')
Pipe length	Max				
	Height difference				
ADD Refrigerant AMOUNT	Max. (OD lower)	m	15	15	30
	Max. (OD higher)	m	15	15	30
PIPE LENGTH FOR ADDITIONAL Refrige			5	5	5
	Rango de operación				
	Tª ext. refrigeración	°C	-15~48	-15~48	-15~48
	Tª ext. calefacción	°C	-15~24	-15~24	-15~24

## Gama Comercial Suelo-Techo

			AUV105UR4RAB4	AUV125UR4RTC5	AUV140UR6RPC4	AUV175UR6RPC4
Unidad interior			AUV105UR4RB4	AUV125UR4RC4	AUV140UR4RC4	AUV175UR4RC4
Unidad exterior			AUW105U4RA4	AUW125U4RT5	AUW140U6RP4	AUW175U6RP4
Capacidad	Frío Nominal (Mín-Máx)	Frig/h	8600(3010—9460)	10578(2838—11352)	12298(2666—13846)	14620(2838—15480)
	Frío Nominal (Mín-Máx)	kW	10000(3500-11000)	12700 (3300-13200)	14300 (3100~16100)	17000 (3300~18000)
	Calor Nominal (Mín-Máx)	Kcal/h	9718(2856—10320)	11610(2580—12556)	14362(3096—15480)	15480(2580—16340)
	Calor Nominal (Mín-Máx)	kW	11300 (3320-12000)	13500 (3000-14600)	16700 (3600~18000)	18000 (3000~19000)
Consumo Nominal			6,1	---	---	---
	SEER (Rango)		4,0	---	---	---
	SCOP (Rango)*		A++	---	---	---
Clasificación Energética	Frío	Frig/h	A+	---	---	---
	Calor	Kcal/h	1700/1500/1300	2000/1800/1600	2000/1600/1200	000/1700/1500
Unidad Interior	Caudal de aire (A/M/B)	m³/min	55/53/51	53/50/47	55/51/48	55/51/48
	Nivel sonoro (A/M/B)	dB(A)	65	66	68	67
	Potencia sonora	dB(A)	1285×680×230	1580×680×230	1580×680×230	1580×680×230
	Dimensiones An x Al x Fon	mm	37.0/44.0	48.0/56.0	48.0/56.0	48.0/56.0
	Peso Neto/con embalaje	kg				
Unidad Exterior			57	62	59	63
	Nivel sonoro (A)	dB(A)	70	75	73	77
	Potencia sonora	dB(A)	950×840×340	950×1050×340	950×1386×340	0×1386×340
	Dimensiones An x Alx Fon	mm	70.0/75.0	85.0/97.0	101.5/114.5	109.0/122.0
	Peso Neto/con embalaje	kg	R32	R32	R32	R32
Refrigerante	Gas		2,00	2,50	3,00	3,40
	Carga Kg		*9.52/*19.05(3/8'/3/4')	*9.52/*19.05(3/8'/3/4')	*9.52/*19.05(3/8'/3/4')	*9.52/*19.05(3/8'/3/4')
Diám. tuberías líquido/gas	mm/pulg		*6.35/*12.7(1/4'/1/2')	*9.52/*15.88(3/8'/5/8')	*9.52/*15.88(3/8'/5/8')	
Pipe length	Max					
	Height difference					
ADD Refrigerant AMOUNT	Max. (OD lower)	m	15	15	30	50
	Max. (OD higher)	m	15	15	30	30
PIPE LENGTH FOR ADDITIONAL Refrige			5	5	5	5
	Rango de operación					
	Tª ext. refrigeración	°C	-15~48	-15~48	-15~48	-15~48
	Tª ext. calefacción	°C	-15~24	-15~24	-15~24	-15~24